

AL 4000 FLOODLIGHT SYSTEM



amida

simple, available and cost effective

Americas Most Economical Full-Sized Mobile Light Tower

The AL 4000 has been engineered to meet the specific needs of the construction industry and is particularly popular with rental dealers.

A full-sized, 30' (9.1 m) extended height floodlighting tower that is easy to move by hand, the AL 4000 produces enough light to illuminate 7-1/2 acres. Other advantages include:

Safe, Rugged Design

Designed and built to exacting standards of safety and structural integrity. Can take the punishment, regardless of job and climactic conditions.

Excellent Investment

Amida light towers have the lowest depreciation rate in the industry. As a result, they hold their value much better than competitive towers.

Amida – your best choice for simple to use, readily available and cost effective jobsite lighting.



360° Rotatable

Light fixtures are securely mounted on mast for travel (A) or can be left on crossarm. Pallet pockets and lifting eye (B) make unit easier to load and unload.



amida

simple, available and cost effective




Retractable power cord automatically recoils into protective sleeve to prevent damage when raising, lowering and moving tower.



Galvanized outriggers with pre-set position stops insure quick and proper spacing for safe operation in heavy winds.




Plug-in ballasts installed in galvanized steel boxes. Can be replaced without disconnecting wiring terminals.



Spring-loaded pin automatically locks galvanized 360° rotatable tower in upright position.



Light fixtures plug into **weatherproof receptacle box** at top of tower with UL and CSA-approved connectors.



Cabinet doors have **gas shock cylinder** for maximum control.



Winch handle **ergonomically positioned** for easy raising and lowering of tower. Winch drum located inside cabinet. Electric safety winch available.



Control panel is inside, away from the elements. Houses main and branch circuit breakers and hourmeter.



30-gallon fuel tank provides 60 hours of continuous run time. Has large diameter filler neck for oversized nozzles.

Buy The Equipment Contractors Rent Most.

Amida floodlight systems are designed with the rental customer in mind. Since more contractors rent Amida than any other brand, it's not surprising what system they choose when they're ready to buy.

Worldwide Distribution Network Provides Parts and Service

With a network of factory-trained distributors and dealers in many of the major markets around the world, Terex Amida can provide parts and service assistance to help keep downtime at a minimum. Terex Amida products also carry a full-year limited warranty on parts and labor.

We reserve the right to amend these specifications at any time without notice. The only warranty applicable is our standard written warranty applicable to the particular product and sale. We make no other warranty, expressed or implied.

AL 4000 Specifications

| | |
|---|---------------------|
| Overall length, travel position w/fixtures & tongue | 179" (455 cm) |
| Overall length, tower vertical w/tongue & jacks | 124" (315 cm) |
| Trailer frame length | 70" (178 cm) |
| Overall height, floodlighting position | 30' (9.14 m) |
| Overall height, travel position | 68" (173 cm) |
| Overall width with fenders | 61" (155 cm) |
| Overall width with outriggers pulled out | 102" (259 cm) |
| Trailer frame width | 41" (104 cm) |
| Tongue length | 44" (112 cm) |
| Wheel size | 15" (38 cm) |
| Axle rating | 3500 lbs. (1588 kg) |
| Tongue weight travel position | 100 lbs. (45 kg) |
| Total weight no fuel | 2050 lbs. (930 kg) |
| Fuel capacity | 30 gal. (114 l) |

For more information, product demonstration, or details on purchase, lease and rental plans, please contact your local Terex Amida Distributor.



TEREX LIGHT CONSTRUCTION

USA & Latin America
 P. O. Box 3147 • Rock Hill, SC 29732 USA
 803-324-3011 • Fax: 803-366-1101
 Call toll-free 1-800-433-3026

Canada & International
 31 Sun Pac Boulevard
 Brampton, Ontario L6S 5P6 CANADA
 905-458-5455 • Fax: 905-458-5484

www.terex.com